



Dressing 75m² of Tasmanian Oak in Satin

Taking care of your timber

This Melbourne home had 75m² of Tasmanian Oak on their ground floor that need re coating it had previously had an old polyurethane coating.

The home owner wanted a natural soft silky finish that was non-yellowing and bought out the natural beauty of the timber.

Renick Ryan, owner of Forest Floors and his experienced crew chose the **Urethane Coatings Waterkote[®] Sealer** in order to maintain natural colour of the timber and finished with **Waterkote[™] Satin** ensuring the soft silky finish the home owner desired.

Renick said he chose **Urethane Coatings Waterkote[®]** materials as they were *High Grade, High Performance products* that delivered an *excellent finish*.

Urethane Coatings WaterKote[®] range of products are non-hazardous, non-yellowing water based polyurethane coatings.



WaterKote[®] - an effective and durable non-hazardous alternative whilst retaining the hard wearing benefits of a solvent based system

A Beautiful Natural Satin Finish



WaterKote[®] SEALER	1 component primer/first (sealing) coat
	Extended open time
	Excellent flow and levelling
	Reduces the risk of edge bonding and tannin bleed
	Retains the natural colour of timber
	Reduced sheen finish prevents 'misses' in the next coat
	Subsequent coats remain on the surface maximising the wear layer
WaterKote[®] 2K SATIN	A NEW generation 2 component water borne polyurethane
	Extended open time
	Exceptional flow and levelling.
	Can be walked on after 24 hours
	Full Cure 5 - 7 days after application

For more information:
www.urethanecoatings.com.au
 +61 2 9666 3788