

# **ERAPOL L-ETX80D PREPOLYMER**

# **Era Polymers Pty Ltd**

Chemwatch: 9-56537 Version No: 1.1

Safety Data Sheet according to WHS and ADG requirements

# Chemwatch Hazard Alert Code: 2

Issue Date: 08/05/2014 Print Date: 08/05/2014 Initial Date: Not Available S.GHS.AUS.EN

# SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

#### **Product Identifier**

Product name	ERAPOL L-ETX80D PREPOLYMER			
Chemical Name	ot Applicable			
Synonyms	Not Available			
Proper shipping name	Not Applicable			
Chemical formula	Not Applicable			
Other means of identification	Not Available			
CAS number	Not Applicable			

# Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Use according to manufacturer's directions. Polyurethane prepolymer

#### Details of the supplier of the safety data sheet

Registered company name	Era Polymers Pty Ltd
Address	25-27 Green Street 2019 NSW Australia
Telephone	+61 (0)2 9666 3788
Fax	+61 (0)2 9666 4805
Website	www.erapol.com.au
Email	erapol@erapol.com.au

# Emergency telephone number

Association / Organisation	CHEMWATCH		
Emergency telephone numbers	Not Available	1	1
Other emergency telephone numbers	Not Available	1	1

# **CHEMWATCH EMERGENCY RESPONSE**

Primary Number	Alternative Number 1	Alternative Number 2	
1800 039 008	+612 9186 1132	Not Available	

Once connected and if the message is not in your prefered language then please dial 01

# **SECTION 2 HAZARDS IDENTIFICATION**

# Classification of the substance or mixture

HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the Model WHS Regulations and the ADG Code.

Poisons Schedule	S6		
GHS Classification [1]	Acute Toxicity (Inhalation) Category 4, Respiratory Sensitizer Category 1, Carcinogen Category 2		
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HSIS; 3. Classification drawn from EC Directive 1272/2008 - Annex VI		

### Label elements

GHS label elements



# Issue Date: **08/05/2014**Print Date: **08/05/2014**

#### **ERAPOL L-ETX80D PREPOLYMER**

SIGNAL WORD	DANGER

#### Hazard statement(s)

H332	Harmful if inhaled	
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled	
H351	Suspected of causing cancer	

# Precautionary statement(s): Prevention

P101	If medical advice is needed, have product container or label at hand.		
P102	Keep out of reach of children.		
P103	Read label before use.		
P201	Obtain special instructions before use.		
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.		
P271	Use only outdoors or in a well-ventilated area.		
P280	Wear protective gloves/protective clothing/eye protection/face protection.		
P284	[In case of inadequate ventilation] wear respiratory protection.		

# Precautionary statement(s): Response

P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.		
P308+P313	Exposed or concerned: Get medical advice/attention.		
P342+P311	If experiencing respiratory symptoms: Call a POISON CENTER/doctor/physician/first aider		
P312	Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.		

#### Precautionary statement(s): Storage

P405 Store locked up.

#### Precautionary statement(s): Disposal

**P501** Dispose of contents/container to authorised chemical landfill or if organic to high temperature incineration

# **SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS**

#### Substances

See section below for composition of Mixtures

# **Mixtures**

CAS No	%[weight]	Name		
Not Available	>60	Polyurethane prepolymer (TDI/PTMEG)		
584-84-9	<1	toluene-2,4-diisocyanate		

# **SECTION 4 FIRST AID MEASURES**

# Description of first aid measures

Eye Contact	If this product comes in contact with eyes:  ▶ Wash out immediately with water.  ▶ If irritation continues, seek medical attention.  ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin or hair contact occurs:  ▶ Flush skin and hair with running water (and soap if available).  ▶ Seek medical attention in event of irritation.
Inhalation	<ul> <li>If fumes or combustion products are inhaled remove from contaminated area.</li> <li>Lay patient down. Keep warm and rested.</li> <li>Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>Transport to hospital, or doctor.</li> <li>Following uptake by inhalation, move person to an area free from risk of further exposure. Oxygen or artificial respiration should be administered as needed. Asthmatic-type symptoms may develop and may be immediate or delayed up to several hours. Treatment is essentially symptomatic. A physician should be consulted.</li> </ul>
Ingestion	<ul> <li>Immediately give a glass of water.</li> <li>First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.</li> </ul>

# Indication of any immediate medical attention and special treatment needed

Toluene diisocyanate is a known pulmonary sensitiser. Annual medical surveillance should be conducted including pulmonary history, examination of the heart and lungs,  $14 \times 17$  inch  $(35 \times 47$  cm) x-ray and pulmonary function testing (FCV, FEV1).

In normal commercial preparations of toluene diisocyanate, the 2,4-isomer dominates in the ratio 4:1. However it is also hydrolysed, in air , more rapidly than the 2,6-isomer. Airway sensitivities may result from the appearance of immunoglobulins in the blood. Frequent inability to detect antibodies to TDI in clinical cases may result from the routine use of diagnostic antigens containing predominantly 2,4-TDI, whereas individuals

# **ERAPOL L-ETX80D PREPOLYMER**

Issue Date: 08/05/2014 Print Date: 08/05/2014

may have been exposed to atmospheres in which 2,6-TDI was the predominant isomer. [Karol & Jin, Frontiers of Molecular Toxicology, pp 55-61, 1992]

# **SECTION 5 FIREFIGHTING MEASURES**

# Extinguishing media

- ▶ There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area

### Special hazards arising from the substrate or mixture

Fire Incompatibility

None known

#### Advice for firefighters

# Fire Fighting

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves in the event of a fire.
- Prevent, by any means available, spillage from entering drains or water courses.
- Use fire fighting procedures suitable for surrounding area.
- ▶ DO NOT approach containers suspected to be hot.
- Fire/Explosion Hazard
- Non combustible. ▶ Not considered a significant fire risk, however containers may burn.

May emit poisonous fumes.

# **SECTION 6 ACCIDENTAL RELEASE MEASURES**

#### Personal precautions, protective equipment and emergency procedures

# Minor Spills

- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- ▶ Control personal contact with the substance, by using protective equipment.
- ▶ Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.

# **Major Spills**

#### Moderate hazard.

- Clear area of personnel and move upwind.
- ▶ Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

# **SECTION 7 HANDLING AND STORAGE**

# Precautions for safe handling

# Safe handling

- ▶ Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- ▶ Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.

Other information

# Conditions for safe storage, including any incompatibilities

Suitable container

- ▶ Polyethylene or polypropylene container.
- Packing as recommended by manufacturer.
- ▶ Check all containers are clearly labelled and free from leaks.

Storage incompatibility

- ▶ NOTE: May develop pressure in containers; open carefully. Vent periodically.
- Segregate from alcohol, water.

# PACKAGE MATERIAL INCOMPATIBILITIES

Not Available

# **SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION**

# **Control parameters**

# OCCUPATIONAL EXPOSURE LIMITS (OEL)

# INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	toluene-2,4-diisocyanate	Isocyanates, all (as-NCO)	0.02 (mg/m3)	0.07 (mg/m3)	Not Available	Not Available

#### **EMERGENCY LIMITS**

Ingredient TEEL-0 TEEL-1 TEEL-2 TEEL-3
--

Page 4 of 7

# **ERAPOL L-ETX80D PREPOLYMER**

Issue Date: 08/05/2014
Print Date: 08/05/2014

toluene-2,4-diisocyanate	0.005 / 0.25(ppm)	0.75 / 0.02(ppm)	1.5 / 0.083(ppm)	0.51 / 1.5(ppm)
Ingredient	Original IDLH		Revised IDLH	
ERAPOL L-ETX80D PREPOLYMER	Not Available		Not Available	

# **Exposure controls**

# Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly.

#### Personal protection











# Eye and face protection

Safety glasses with side shields

Chemical goggles

Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available.

#### Skin protection

See Hand protection below

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when

# Hand protection

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:

- frequency and duration of contact,
- chemical resistance of glove material,
- glove thickness and

making a final choice.

dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).

# Body protection

See Other protection below

• Overalls

# Other protection

- P.V.C. apron.
- Barrier cream.
- ▶ Skin cleansing cream.

# Thermal hazards

Not Available

# Recommended material(s)

#### **GLOVE SELECTION INDEX**

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the *computer-generated* selection:

ERAPOL L-ETX80D PREPOLYMER Not Available

Material	CPI

\* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

# Respiratory protection

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A-AUS P2	-	A-PAPR-AUS / Class 1 P2
up to 50 x ES	-	A-AUS / Class 1 P2	-
up to 100 x ES	-	A-2 P2	A-PAPR-2 P2 ^

# ^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

# **SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES**

Chemwatch: 9-56537 Version No: 1.1

# **ERAPOL L-ETX80D PREPOLYMER**

Issue Date: 08/05/2014 Print Date: 08/05/2014

Appearance	Clear pale amber		
Appearance	Clear pale arriber		
Physical state	Liquid	Relative density (Water = 1)	1.10
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Reacts	pH as a solution(1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

# **SECTION 10 STABILITY AND REACTIVITY**

Reactivity	See section 7
Chemical stability	<ul> <li>Presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

# **SECTION 11 TOXICOLOGICAL INFORMATION**

toluene-2,4-diisocyanate

Information on toxicological effects		
Inhaled	The material is not thought to produce resp	nes), generated by the material during the course of normal handling, may be harmful. iratory irritation (as classified by EC Directives using animal models). Nevertheless inhalation of rolonged periods, may produce respiratory discomfort and occasionally, distress.
Ingestion	<u> </u>	erse health effects following ingestion (as classified by EC Directives using animal models).  be been produced following exposure of animals by at least one other route and good hygiene practice  n.
Skin Contact	has been identified following exposure of an through wounds, lesions or abrasions. Good occupational setting. Open cuts, abraded or irritated skin should r Entry into the blood-stream through, for exal	ful health effects (as classified under EC Directives using animal models). Systemic harm, however, imals by at least one other route and the material may still produce health damage following entry I hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an not be exposed to this material mple, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects.
Еуе	Although the liquid is not thought to be an ir characterised by tearing or conjunctival red	ritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort ness (as with windburn).
Chronic	respect of the available information, howeve Practical evidence shows that inhalation of t greater frequency than would be expected fr Pulmonary sensitisation, resulting in hyperac Significant symptoms of exposure may persi	its, concern has been expressed that the material may produce carcinogenic or mutagenic effects; in r, there presently exists inadequate data for making a satisfactory assessment. the material is capable of inducing a sensitisation reaction in a substantial number of individuals at a om the response of a normal population. tive airway dysfunction and pulmonary allergy may be accompanied by fatigue, malaise and aching, st for extended periods, even after exposure ceases. Symptoms can be activated by a variety of thomobile exhaust, perfumes and passive smoking.
ERAPOL L-ETX80D PREPOLYMER	TOXICITY	IRRITATION
	Not Available	Not Available
	TOXICITY	IRRITATION
	Inhalation (rat) I C50: 14 ppm/14 hr	Eve (rabbit): 100 mg - SEVERE

Eye (rabbit): 100 mg - SEVERE

Not Available

Skin (rabbit): 500 mg(open)-SEVERE

Skin (rabbit):500 mg/24hr-moderate

Inhalation (rat) LC50: 14 ppm/14 hr

Inhalation (rat) LC50: 600 ppm/6 hr

Oral (rat) LD50: 5800 mg/kg

Not Available

# Page 6 of 7 **ERAPOL L-ETX80D PREPOLYMER**

Issue Date: 08/05/2014 Print Date: 08/05/2014

FRAPOL L-FTX80D PREPOLYMER				
	EDADOL	I ETVOND	DDEDOI V	MED

Allergic reactions which develop in the respiratory passages as bronchial asthma or rhinoconjunctivitis, are mostly the result of reactions of the allergen with specific antibodies of the IgE class and belong in their reaction rates to the manifestation of the immediate type. In addition to the allergen-specific potential for causing respiratory sensitisation, the amount of the allergen, the exposure period and the genetically determined disposition of the exposed person are likely to be decisive. Factors which increase the sensitivity of the mucosa may play a role in predisposing a person to allergy. They may be genetically determined or acquired, for example, during infections or exposure to irritant substances. Immunologically the low molecular weight substances become complete allergens in the organism either by binding to peptides or proteins (haptens) or after metabolism (prohaptens).

#### **TOLUENE-2,4-DIISOCYANATE**

The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important.

Acute Toxicity	✓	Carcinogenicity	✓
Skin Irritation/Corrosion	0	Reproductivity	0
Serious Eye Damage/Irritation	0	STOT - Single Exposure	0
Respiratory or Skin sensitisation	✓	STOT - Repeated Exposure	0
Mutagenicity	0	Aspiration Hazard	0

#### **CMR STATUS**

CARCINOGEN

toluene-2,4-diisocyanate

Australia Exposure Standards - Carcinogens

#### **SECTION 12 ECOLOGICAL INFORMATION**

# Toxicity

DO NOT discharge into sewer or waterways.

# Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
Not Available	Not Available	Not Available

# **Bioaccumulative potential**

Ingredient	Bioaccumulation
Not Available	Not Available

#### Mobility in soil

Ingredient	Mobility
Not Available	Not Available

# **SECTION 13 DISPOSAL CONSIDERATIONS**

#### Waste treatment methods

▶ Containers may still present a chemical hazard/ danger when empty. • Return to supplier for reuse/ recycling if possible.

Otherwise:

Product / Packaging disposal

- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
- ▶ Where possible retain label warnings and MSDS and observe all notices pertaining to the product.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory.

# **SECTION 14 TRANSPORT INFORMATION**

#### Labels Required

<u> </u>	
Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

# **SECTION 15 REGULATORY INFORMATION**

Version No: 1.1

#### **ERAPOL L-ETX80D PREPOLYMER**

Issue Date: **08/05/2014**Print Date: **08/05/2014** 

#### Safety, health and environmental regulations / legislation specific for the substance or mixture

"Australia Inventory of Chemical Substances (AICS)","Australia Hazardous Substances Information System - Consolidated Lists", "Australia National Pollutant Inventory", "OECD Existing Chemicals Database", "OECD List of High Production Volume (HPV) Chemicals", "Australia High Volume Industrial Chemical List (HVICL)", "International Council of Chemical Associations (ICCA) - High Production Volume List", "FisherTransport Information", "Sigma-AldrichTransport Information", "GESAMP/EHS Composite List - GESAMP Hazard Profiles","International Maritime Dangerous Goods Requirements (IMDG Code) - Substance Index","Australia - Victoria Occupational Health and Safety Regulations - Schedule 9: Materials at Major Hazard Facilities (And Their Threshold Quantity) Table 1","Australia - South Australia -Work Health and Safety Regulations 2012 - Schedule 15—Hazardous chemicals at major hazard facilities (and their threshold quantity) Table 15.1","Australia - New South Wales - Work Health and Safety Regulation 2011 - Hazardous chemicals at major hazard facilities (and their threshold quantity) - Table 15.1","International Air Transport Association (IATA) Dangerous Goods Regulations","International Maritime Dangerous Goods Requirements (IMDG Code)", "Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes", "Belgium Federal Public Service Mobility and Transport, Regulations concerning the International Carriage of Dangerous Goods by Rail - Table A: Dangerous Goods List - RID 2013 (Dutch)","Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List","International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs","IMO IBC Code Chapter 17: Summary of minimum requirements", "Australia - Queensland Work Health and Safety Regulation - Hazardous chemicals at major hazard facilities (and their threshold quantity)", "Australia Work Health and Safety Regulations 2011 - Hazardous chemicals at major hazard facilities and their threshold quantity", "Australia - Tasmania - Work Health and Safety Regulations 2012 - Hazardous Chemicals at Major Hazard Facilities (and their Threshold Quantity) - Table 15.1","Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6","Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix F (Part 3)","Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2)","Australia Occupational Health and Safety (Commonwealth Employment) (National Standards) Regulations 1994 - Hazardous Substances Requiring Health Surveillance", "Australia Hazardous Substances Requiring Health Surveillance", "Australia - Tasmania - Work Health and Safety Regulations 2012 - Requirements for Health Monitoring - Hazardous chemicals (other than lead) requiring health monitoring","Australia - South Australia - Work Health and Safety Regulations 2012 - Requirements for health monitoring - Hazardous chemicals (other than lead) requiring health monitoring", "Australia Work Health and Safety Regulations 2011 -Hazardous chemicals (other than lead) requiring health monitoring", "Australia - Northern Territories Work Health and Safety National Uniform Legislation Regulations- Requirements for health monitoring - Hazardous chemicals (other than lead) requiring health monitoring"."Australia -Queensland Work Health and Safety Regulation - Hazardous chemicals (other than lead) requiring health monitoring", "Australia - New South Wales - Work Health and Safety Regulation 2011 - Requirements for health monitoring -Hazardous chemicals (other than lead) requiring health monitoring","Australia - Western Australia Hazardous Substances Requiring Health Surveillance","Australia - New South Wales Hazardous Substances Requiring Health Surveillance", "Australia - Tasmania Hazardous Substances Requiring Health Surveillance", "Australia Exposure Standards"

toluene-2,4-diisocyanate(584-84-9) is found on the following regulatory lists

#### **SECTION 16 OTHER INFORMATION**

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.