



A Satin Finish for Blackbutt

Taking care of your timber

Blackbutt is a beautiful native Australian hardwood with an appealing colour palette from cream to pale brown with a hint of pink and a relatively straight and uniform grain pattern. It is commonly used for both structural and exterior applications as well as timber flooring.

Blackbutt is not only appealing to designers and home owners for its aesthetics and incredible durability, it is also a good plantation timber as it is quick to grow and is readily available in New South Wales and Southern Queensland.

This home had 200m² of Blackbutt timber flooring that needed protecting, the owner wanted to retain the natural beauty of the wood while achieving a soft silky finish

that would work with their contemporary styling.

The contractor chose **Urethane Coatings Waterkote® Sealer** in order to maintain natural colour of the timber and finished with **Waterkote® 2K Satin** ensuring the finish the home owner desired.

Once prepared the timber was sealed with **WaterKote® Sealer** a primer and sealing coat which ensures that subsequent coats remain on the surface therefore maximising the wear layer. The seal coat was followed with 2 coats of **WaterKote® 2K Satin** resulting in a natural Satin finish.



WaterKote® - An effective & durable non-hazardous alternative whilst retaining the hard wearing benefits of a solvent based system



WaterKote® - SEALER

1 component primer/ first (sealing) coat



- Reduces the risk of edge bonding & tannin bleed
- Retains the natural colour of timber
- Subsequent coats remain on the surface maximising the wear layer

WaterKote® 2K SATIN

A NEW generation 2 Component water borne polyurethane



- Exceptional flow & levelling
- Full cure: 5-7 days after application. Return to service