



ERAPOL GL65A POLYOL

Era Polymers Pty Ltd

Version No: 2.4

Safety Data Sheet according to WHS and ADG requirements

Chemwatch Hazard Alert Code: 3

Issue Date: 20/01/2016

Print Date: 07/03/2016

Initial Date: 13/08/2014

S.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	ERAPOL GL65A POLYOL
Synonyms	Not Available
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Polyurethane polyol
--------------------------	---------------------

Details of the supplier of the safety data sheet

Registered company name	Era Polymers Pty Ltd
Address	25-27 Green Street 2019 NSW Australia
Telephone	+61 (0)2 9666 3788
Fax	+61 (0)2 9666 4805
Website	www.erapol.com.au
Email	erapol@erapol.com.au

Emergency telephone number

Association / Organisation	CHEMWATCH
Emergency telephone numbers	Not Available
Other emergency telephone numbers	Not Available

CHEMWATCH EMERGENCY RESPONSE

Primary Number	Alternative Number 1	Alternative Number 2
1800 039 008	+612 9186 1132	Not Available

Once connected and if the message is not in your preferred language then please dial 01

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

Poisons Schedule	Not Applicable
Classification ^[1]	Skin Sensitizer Category 1, Serious Eye Damage Category 1, Acute Aquatic Hazard Category 3, Chronic Aquatic Hazard Category 3
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HSIS; 3. Classification drawn from EC Directive 1272/2008 - Annex VI

Label elements

GHS label elements	
--------------------	--

SIGNAL WORD **DANGER**

Continued...

ERAPOL GL65A POLYOL

Hazard statement(s)

H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H402	Harmful to aquatic life
H412	Harmful to aquatic life with long lasting effects

Precautionary statement(s) Prevention

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P272	Contaminated work clothing should not be allowed out of the workplace.

Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.
P363	Wash contaminated clothing before reuse.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

P501	Dispose of contents/container in accordance with local regulations.
------	---

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
Not Available	>60	Polyol blend - non-hazardous
2530-83-8	1-10	<u>gamma-glycidoxypropyltrimethoxysilane</u>
41556-26-7	1-10	<u>bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate</u>
10584-98-2	<0.3	<u>dibutyltin bis(2-ethylhexyl mercaptoacetate)</u>
27236-65-3	<1	<u>bis(phenylmercury) dodeceny succinate</u>

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> ▶ Immediately hold eyelids apart and flush the eye continuously with running water. ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▶ Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. ▶ Transport to hospital or doctor without delay. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	<p>If skin contact occurs:</p> <ul style="list-style-type: none"> ▶ Immediately remove all contaminated clothing, including footwear. ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation.
Inhalation	<ul style="list-style-type: none"> ▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area. ▶ Other measures are usually unnecessary.
Ingestion	<ul style="list-style-type: none"> ▶ Immediately give a glass of water. ▶ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

For acute and short term repeated exposures to aryl and alkylmethoxy compounds of mercury: Absorption proceeds more rapidly than its inorganic counterpart but once inside the body biotransformation releases inorganic mercury. [Ellenhorn and Barceloux: Medical Toxicology]

- ▶ Moderate adsorption of inorganic mercury compounds through the gastro-intestinal tract (7-15%) is the principal cause of poisoning. These compounds are highly concentrated (as the mercuric (Hg (2+) form) in the kidney; acute ingestion may lead to oliguric renal failure. Severe mucosal necrosis may also result from ingestion.

Continued...

ERAPOL GL65A POLYOL

- ▶ Chronic effects range from proteinuria to nephrotic syndrome. Chronic presentation also involves dermatitis, gingivitis, stomatitis, tremor and neuropsychiatric symptoms of erethism.
- ▶ Absorbed inorganic mercury does not significantly cross the blood-brain barrier.
- ▶ Emesis and lavage should be initiated following acute ingestion.
- ▶ Activated charcoal interrupts absorption; cathartics should be administered when charcoal is given.
- ▶ The use of British Anti-Lewisite is indicated in severe inorganic poisoning. Newer derivatives of BAL (e.g. dimercaptosuccinic acid, [DMSA] and 2,3-dimercapto-1-propanesulfate [DMPS]) may prove more effective. [Ellenhorn and Barceloux: Medical Toxicology]

BIOLOGICAL EXPOSURE INDEX - BEI

These represent the determinants observed in specimens from a healthy worker exposed at the Exposure Standard (ES or TLV).

Determinant	Index	Sampling Time	Comments
1. Total inorganic mercury in urine	35 ug/gm creatinine	Preshift	B
2. Total inorganic mercury in blood	15 ug/L	End of shift at end of workweek	B

B: Background levels occur in specimens collected from subjects **NOT** exposed.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

- ▶ There is no restriction on the type of extinguisher which may be used.
- ▶ Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.
----------------------	-------------

Advice for firefighters

Fire Fighting	<ul style="list-style-type: none"> ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ Wear breathing apparatus plus protective gloves in the event of a fire. ▶ Prevent, by any means available, spillage from entering drains or water courses. ▶ Use fire fighting procedures suitable for surrounding area. ▶ DO NOT approach containers suspected to be hot. ▶ Cool fire exposed containers with water spray from a protected location. ▶ If safe to do so, remove containers from path of fire. ▶ Equipment should be thoroughly decontaminated after use.
Fire/Explosion Hazard	<ul style="list-style-type: none"> ▶ Non combustible. ▶ Not considered a significant fire risk, however containers may burn. May emit corrosive fumes.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Minor Spills	<ul style="list-style-type: none"> ▶ Clean up all spills immediately. ▶ Avoid breathing vapours and contact with skin and eyes. ▶ Control personal contact with the substance, by using protective equipment. ▶ Contain and absorb spill with sand, earth, inert material or vermiculite. ▶ Wipe up. ▶ Place in a suitable, labelled container for waste disposal.
Major Spills	<p>Moderate hazard.</p> <ul style="list-style-type: none"> ▶ Clear area of personnel and move upwind. ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ Wear breathing apparatus plus protective gloves. ▶ Prevent, by any means available, spillage from entering drains or water course. ▶ Stop leak if safe to do so. ▶ Contain spill with sand, earth or vermiculite. ▶ Collect recoverable product into labelled containers for recycling. ▶ Neutralise/decontaminate residue (see Section 13 for specific agent). ▶ Collect solid residues and seal in labelled drums for disposal. ▶ Wash area and prevent runoff into drains. ▶ After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using. ▶ If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	<ul style="list-style-type: none"> ▶ Avoid all personal contact, including inhalation. ▶ Wear protective clothing when risk of exposure occurs. ▶ Use in a well-ventilated area. ▶ Avoid contact with moisture. ▶ Avoid contact with incompatible materials. ▶ When handling, DO NOT eat, drink or smoke. ▶ Keep containers securely sealed when not in use. ▶ Avoid physical damage to containers. ▶ Always wash hands with soap and water after handling. ▶ Work clothes should be laundered separately. Launder contaminated clothing before re-use. ▶ Use good occupational work practice. ▶ Observe manufacturer's storage and handling recommendations contained within this SDS.
---------------	--

ERAPOL GL65A POLYOL

	<ul style="list-style-type: none"> ▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained. ▶ DO NOT allow clothing wet with material to stay in contact with skin
Other information	

Conditions for safe storage, including any incompatibilities

Suitable container	<ul style="list-style-type: none"> ▶ Polyethylene or polypropylene container. ▶ Packing as recommended by manufacturer. ▶ Check all containers are clearly labelled and free from leaks.
Storage incompatibility	<ul style="list-style-type: none"> ▶ WARNING: Avoid or control reaction with peroxides. All <i>transition metal</i> peroxides should be considered as potentially explosive. For example transition metal complexes of alkyl hydroperoxides may decompose explosively. ▶ The pi-complexes formed between chromium(0), vanadium(0) and other transition metals (haloarene-metal complexes) and mono- or poly-fluorobenzene show extreme sensitivity to heat and are explosive. ▶ Avoid reaction with borohydrides or cyanoborohydrides

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	dibutyltin bis(2-ethylhexyl mercaptoacetate)	Tin, organic compounds (as Sn)	0.1 mg/m ³	0.2 mg/m ³	Not Available	Sk
Australia Exposure Standards	bis(phenylmercury) dodeceny succinate	Mercury, aryl compounds (as Hg)	0.1 mg/m ³	Not Available	Not Available	Sk

EMERGENCY LIMITS


Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
gamma-glycidoxypropyltrimethoxysilane	Glycidoxypropyltrimethoxysilane; (3-(2,3-Epoxypropoxy) propyltrimethoxysilane)	1.7 mg/m ³	19 mg/m ³	210 mg/m ³

Ingredient	Original IDLH	Revised IDLH
Polyol blend - non-hazardous	Not Available	Not Available
gamma-glycidoxypropyltrimethoxysilane	Not Available	Not Available
bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	Not Available	Not Available
dibutyltin bis(2-ethylhexyl mercaptoacetate)	Unknown mg/m ³ / Unknown ppm	25 mg/m ³
bis(phenylmercury) dodeceny succinate	28 mg/m ³	10 mg/m ³

Exposure controls

Appropriate engineering controls	<p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.</p> <p>Employers may need to use multiple types of controls to prevent employee overexposure.</p> <p>General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.</p>										
	<table border="1"> <thead> <tr> <th>Type of Contaminant:</th> <th>Air Speed:</th> </tr> </thead> <tbody> <tr> <td>solvent, vapours, degreasing etc., evaporating from tank (in still air)</td> <td>0.25-0.5 m/s (50-100 f/min)</td> </tr> <tr> <td>aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)</td> <td>0.5-1 m/s (100-200 f/min.)</td> </tr> <tr> <td>direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)</td> <td>1-2.5 m/s (200-500 f/min)</td> </tr> <tr> <td>grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).</td> <td>2.5-10 m/s (500-2000 f/min.)</td> </tr> </tbody> </table>	Type of Contaminant:	Air Speed:	solvent, vapours, degreasing etc., evaporating from tank (in still air)	0.25-0.5 m/s (50-100 f/min)	aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)	direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min)	grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)
	Type of Contaminant:	Air Speed:									
	solvent, vapours, degreasing etc., evaporating from tank (in still air)	0.25-0.5 m/s (50-100 f/min)									
	aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)									
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min)										
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)										
<p>Within each range the appropriate value depends on:</p> <table border="1"> <thead> <tr> <th>Lower end of the range</th> <th>Upper end of the range</th> </tr> </thead> <tbody> <tr> <td>1: Room air currents minimal or favourable to capture</td> <td>1: Disturbing room air currents</td> </tr> <tr> <td>2: Contaminants of low toxicity or of nuisance value only</td> <td>2: Contaminants of high toxicity</td> </tr> <tr> <td>3: Intermittent, low production.</td> <td>3: High production, heavy use</td> </tr> <tr> <td>4: Large hood or large air mass in motion</td> <td>4: Small hood - local control only</td> </tr> </tbody> </table>	Lower end of the range	Upper end of the range	1: Room air currents minimal or favourable to capture	1: Disturbing room air currents	2: Contaminants of low toxicity or of nuisance value only	2: Contaminants of high toxicity	3: Intermittent, low production.	3: High production, heavy use	4: Large hood or large air mass in motion	4: Small hood - local control only	
Lower end of the range	Upper end of the range										
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents										
2: Contaminants of low toxicity or of nuisance value only	2: Contaminants of high toxicity										
3: Intermittent, low production.	3: High production, heavy use										
4: Large hood or large air mass in motion	4: Small hood - local control only										

ERAPOL GL65A POLYOL

	Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.																					
Personal protection																						
Eye and face protection	<ul style="list-style-type: none"> ▶ Safety glasses with side shields. ▶ Chemical goggles. ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent] 																					
Skin protection	See Hand protection below																					
Hands/feet protection	<p>NOTE:</p> <ul style="list-style-type: none"> ▶ The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact. ▶ Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed. <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p> <p>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</p> <p>Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:</p> <ul style="list-style-type: none"> ▶ frequency and duration of contact, ▶ chemical resistance of glove material, ▶ glove thickness and ▶ dexterity <p>Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).</p> <ul style="list-style-type: none"> ▶ When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. ▶ When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. ▶ Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use. ▶ Contaminated gloves should be replaced. <p>Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p> <p>WARNING: Do NOT use latex or PVC gloves</p> <ul style="list-style-type: none"> ▶ In 1997, a researcher (Dr. Karen E. Wetterhahn) died from organic mercury poisoning, resulting from a single exposure to dimethylmercury almost a year before. ▶ Heavy metals and organic metal compounds, in particular, have posed special hazards in worker protection. At the time of diagnosis and before she lapsed into a vegetative state, Dr. Wetterhahn asked that her case be made known to others. <p>Permeation testing of the potential of transdermal exposure to dimethylmercury produced the following results*.</p> <table border="1" data-bbox="359 1355 1489 1615"> <thead> <tr> <th>Glove material</th> <th>Thickness in mm*</th> <th>Breakthrough Time</th> </tr> </thead> <tbody> <tr> <td>Nitrile</td> <td>0.2</td> <td>0.25 minutes</td> </tr> <tr> <td>Neoprene</td> <td>0.8</td> <td><10 mins.</td> </tr> <tr> <td>Butyl</td> <td>0.33</td> <td><15 mins.</td> </tr> <tr> <td>Viton</td> <td>0.28</td> <td><15 mins.</td> </tr> <tr> <td>Silver Shield</td> <td>0.13</td> <td>>240 mins.</td> </tr> <tr> <td>Silver Shield & Neoprene Pair</td> <td>0.7</td> <td>>240 mins.</td> </tr> </tbody> </table> <p>*Michael B Blayney: Applied Occupational and Environmental Hygiene: 16, pp 233-236, 2001 * Originally quoted as mil (one mil = 0.001 inches)</p>	Glove material	Thickness in mm*	Breakthrough Time	Nitrile	0.2	0.25 minutes	Neoprene	0.8	<10 mins.	Butyl	0.33	<15 mins.	Viton	0.28	<15 mins.	Silver Shield	0.13	>240 mins.	Silver Shield & Neoprene Pair	0.7	>240 mins.
Glove material	Thickness in mm*	Breakthrough Time																				
Nitrile	0.2	0.25 minutes																				
Neoprene	0.8	<10 mins.																				
Butyl	0.33	<15 mins.																				
Viton	0.28	<15 mins.																				
Silver Shield	0.13	>240 mins.																				
Silver Shield & Neoprene Pair	0.7	>240 mins.																				
Body protection	See Other protection below																					
Other protection	<ul style="list-style-type: none"> ▶ Overalls. ▶ P.V.C. apron. ▶ Barrier cream. ▶ Skin cleansing cream. ▶ Eye wash unit. 																					
Thermal hazards	Not Available																					

Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A-AUS P2	-	A-PAPR-AUS / Class 1 P2
up to 50 x ES	-	A-AUS / Class 1 P2	-

ERAPOL GL65A POLYOL

up to 100 x ES	-	A-2 P2	A-PAPR-2 P2 ^
----------------	---	--------	---------------

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Family of products which vary in their physical properties as a result of variations in production. Data presented here is for typical family member. WATER CLEAR LIQUID		
Physical state	Liquid	Relative density (Water = 1)	1.2
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	<ul style="list-style-type: none"> ▶ Unstable in the presence of incompatible materials. ▶ Product is considered stable. ▶ Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.
Ingestion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.
Skin Contact	The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.
Eye	If applied to the eyes, this material causes severe eye damage.
Chronic	Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population.

ERAPOL GL65A POLYOL	TOXICITY	IRRITATION
	Not Available	Not Available
gamma-glycidioxypropyltrimethoxysilane	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 4247.9 mg/kg ^[1]	Not Available
	Oral (rat) LD50: >5350 mg/kg ^[1]	

ERAPOL GL65A POLYOL

bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	TOXICITY	IRRITATION
	Oral (rat) LD50: 3100 mg/kg ^[2]	Nil reported *[Ameron]
dibutyltin bis(2-ethylhexyl mercaptoacetate)	TOXICITY	IRRITATION
	dermal (rat) LD50: 777 mg/kg ^[1]	Not Available
	Oral (rat) LD50: 396 mg/kg ^[1]	
bis(phenylmercury) dodeceny succinate	TOXICITY	IRRITATION
	Not Available	Not Available

Legend: 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

ERAPOL GL65A POLYOL	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested. No significant acute toxicological data identified in literature search.
GAMMA-GLYCIDOXYPROPYLTRIMETHOXSILANE	Low molecular weight alkoxy silane can cause irreversible lung damage when inhaled at low dose. It is not an obvious skin irritant. However, studies suggest with repeated occupational exposure, methoxy silane may cause damage to the eye and skin as well as cancer. For gamma-glycidopropyltrimethoxysilane (GPTMS): GPTMS undergoes rapid hydrolysis and the observed toxicity is expected to be due primarily to methanol and silanetriols. GPTMS is mildly irritating to the skin and eyes and is not a known skin sensitiser in humans or in animals. GPTMS has been shown to cause chromosomal damage and gene mutations. It is not considered to cause tumours. It causes developmental effects, but only at levels which are toxic to the mother. The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.
BIS(PHENYLMERCURY) DODECENYLSUCCINATE	No significant acute toxicological data identified in literature search.
BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL)SEBACATE & DIBUTYLTIN BIS(2-ETHYLHEXYL MERCAPTOACETATE)	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.

Acute Toxicity	☒	Carcinogenicity	☒
Skin Irritation/Corrosion	☒	Reproductivity	☒
Serious Eye Damage/Irritation	☑	STOT - Single Exposure	☒
Respiratory or Skin sensitisation	☑	STOT - Repeated Exposure	☒
Mutagenicity	☒	Aspiration Hazard	☒

Legend: ☒ – Data available but does not fill the criteria for classification
☑ – Data required to make classification available
☒ – Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Ingredient	Endpoint	Test Duration (hr)	Species	Value	Source
gamma-glycidoxypropyltrimethoxysilane	EC50	96	Algae or other aquatic plants	<1.000mg/L	3
gamma-glycidoxypropyltrimethoxysilane	LC50	96	Fish	4.9mg/L	2
gamma-glycidoxypropyltrimethoxysilane	NOEC	96	Fish	1.5mg/L	2
gamma-glycidoxypropyltrimethoxysilane	EC50	48	Crustacea	473mg/L	2
gamma-glycidoxypropyltrimethoxysilane	EC50	168	Algae or other aquatic plants	119mg/L	2
bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	EC0	24	Crustacea	<10mg/L	1

Continued...

ERAPOL GL65A POLYOL

bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	LC50	96	Fish	=0.34mg/L	1
dibutyltin bis(2-ethylhexyl mercaptoacetate)	EC0	48	Crustacea	=0.01mg/L	1
dibutyltin bis(2-ethylhexyl mercaptoacetate)	NOEC	48	Crustacea	=0.01mg/L	1
dibutyltin bis(2-ethylhexyl mercaptoacetate)	EC50	72	Algae or other aquatic plants	=0.56mg/L	1
dibutyltin bis(2-ethylhexyl mercaptoacetate)	LC50	96	Fish	=2.1mg/L	1
dibutyltin bis(2-ethylhexyl mercaptoacetate)	EC50	48	Crustacea	0.035mg/L	2

Legend:

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

Mercury may occur in the environment as free mercury, Hg(0), mercury ions in salts and complexes, Hg⁺ and (Hg₂)²⁺ and as organic mercury compounds. Each species has its own set of physical, chemical and toxicologic properties. In natural systems a dynamic equilibrium between soil and water mercury occurs, determined largely by the physicochemical and biological conditions which pertain.

Mercury ion is transported to aquatic ecosystems via surface run-off and from the atmosphere. It is complexed or tightly bound to both inorganic and organic particles, particularly sediments with high sulfur content. Organic acids such as fulvic and humic acids are often associated with mercury not bound to particles. Methyl mercury is produced by sediment micro-organisms, non-biologically in sediments, and by certain species of fish. The methylation of mercury by micro-organisms is the detoxification response that allows the organism to dispose of the heavy metal ions as small organometallic complexes. Methylation occurs only within a narrow pH range in which the micro-organism might exist and the rate of synthesis depends on the redox potential, composition of the microbial population, availability of Hg²⁺ and temperature. In addition it has been demonstrated that the livers of yellow-fin tuna and albacore produce methyl mercury results in its removal thus little methyl mercury is found in sediments. Demethylation by sediment micro-organisms also occurs at a rapid rate compared with methylation. The best conversion rate for inorganic mercury to methyl mercury under ideal conditions is less than 1.5% per month. Methyl mercury released into surface waters may also be broken down into mercury when exposed to light. Methyl mercury can be bioaccumulated by planktonic algae and fish. In fish, the rate of absorption of methyl mercury is faster than that of inorganic mercury and the clearance rate is slower resulting in high concentrations of methyl mercury in muscle tissue. The ratio of organic mercury to total mercury is generally high in fish compared with other aquatic organisms. Selenium which is also present in seawater and other seafoods readily complexes with methyl mercury and is thought to have a protective effect against the toxic action of methyl mercury. The danger of methyl mercury poisoning has been illustrated in Minimata, Japan in the late 1950s following industrial release of mercury into the bay which subsequently resulted in at least 1200 cases of poisoning, some fatal.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
gamma-glycidioxypropyltrimethoxysilane	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
gamma-glycidioxypropyltrimethoxysilane	LOW (LogKOW = -0.9152)

Mobility in soil

Ingredient	Mobility
gamma-glycidioxypropyltrimethoxysilane	LOW (KOC = 90.22)

SECTION 13 DISPOSAL CONSIDERATIONS**Waste treatment methods**

Product / Packaging disposal	<ul style="list-style-type: none"> ▶ Containers may still present a chemical hazard/ danger when empty. ▶ Return to supplier for reuse/ recycling if possible. <p>Otherwise:</p> <ul style="list-style-type: none"> ▶ If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill. ▶ Where possible retain label warnings and SDS and observe all notices pertaining to the product. <p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.</p> <p>A Hierarchy of Controls seems to be common - the user should investigate:</p> <ul style="list-style-type: none"> ▶ Reduction ▶ Reuse ▶ Recycling ▶ Disposal (if all else fails) <p>This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.</p> <ul style="list-style-type: none"> ▶ DO NOT allow wash water from cleaning or process equipment to enter drains. ▶ It may be necessary to collect all wash water for treatment before disposal. ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. ▶ Where in doubt contact the responsible authority. ▶ Recycle wherever possible. ▶ Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility
-------------------------------------	---

ERAPOL GL65A POLYOL

- ▶ can be identified.
- ▶ Dispose of by: burial in a land-fill specifically licenced to accept chemical and / or pharmaceutical wastes or incineration in a licenced apparatus (after admixture with suitable combustible material).
- ▶ Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

GAMMA-GLYCIDOXYPROPYLTRIMETHOXSILANE(2530-83-8) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Inventory of Chemical Substances (AICS)

BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL)SEBACATE(41556-26-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Inventory of Chemical Substances (AICS)

DIBUTYL TIN BIS(2-ETHYLHEXYL MERCAPTOACETATE)(10584-98-2) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards

Australia Inventory of Chemical Substances (AICS)

Australia Hazardous Substances Information System - Consolidated Lists

BIS(PHENYLMERCURY) DODECENYLSUCCINATE(27236-65-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards

Australia Inventory of Chemical Substances (AICS)

Australia Hazardous Substances Information System - Consolidated Lists

National Inventory	Status
Australia - AICS	Y
Canada - DSL	N (bis(phenylmercury) dodeceny succinate)
Canada - NDSL	N (gamma-glycidoxypropyltrimethoxysilane; bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate; bis(phenylmercury) dodeceny succinate; dibutyltin bis(2-ethylhexyl mercaptoacetate))
China - IECSC	N (bis(phenylmercury) dodeceny succinate)
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	N (bis(phenylmercury) dodeceny succinate)
Korea - KECI	N (bis(phenylmercury) dodeceny succinate)
New Zealand - NZIoC	Y
Philippines - PICCS	Y
USA - TSCA	N (bis(phenylmercury) dodeceny succinate)
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Other information

Ingredients with multiple cas numbers

Name	CAS No
dibutyltin bis(2-ethylhexyl mercaptoacetate)	10584-98-2, 202875-90-9, 52683-17-7

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC – TWA: Permissible Concentration-Time Weighted Average

Continued...

ERAPOL GL65A POLYOL

PC—STEL: Permissible Concentration-Short Term Exposure Limit
IARC: International Agency for Research on Cancer
ACGIH: American Conference of Governmental Industrial Hygienists
STEL: Short Term Exposure Limit
TEEL: Temporary Emergency Exposure Limit
IDLH: Immediately Dangerous to Life or Health Concentrations
OSF: Odour Safety Factor
NOAEL :No Observed Adverse Effect Level
LOAEL: Lowest Observed Adverse Effect Level
TLV: Threshold Limit Value
LOD: Limit Of Detection
OTV: Odour Threshold Value
BCF: BioConcentration Factors
BEI: Biological Exposure Index